












HazLoc Product	DESCRIPTION	DIM	CAT #	WATTS	VOLTS	LUMENS	IP	DLC	CLASS 1	GROUPS	CLASS 2	GROUPS	OTHER	MARINE	AMBIENT	MOUNTING / OPTIONS	
THE BEAST 	The Beast High Bay	20"	HH06-055-50-EX-X-GR	55	120/277,480	6,605	66		Div 2	A, B, C, D	Div 2	F, G	US Made	1958 Wet	65°C	Pendant, Hook, Hood	
	The Beast High Bay	20"	HH12-104-50-EX-X-GR	104	120/277,480	13,406	66		Div 2	A, B, C, D	Div 2	F, G	US Made	1958 Wet	65°C	Pendant, Hook, Hood	
	The Beast High Bay	20"	HH18-170-50-EX-X-GR	170	120/277,480	19,500	66		Div 2	A, B, C, D	Div 2	F, G	US Made	1958 Wet	65°C	Pendant, Hook, Hood	
	The Beast High Bay	20"	HH22-215-50-EX-X-GR	215	120/277,480	24,055	66		Div 2	A, B, C, D	Div 2	F, G	US Made	1958 Wet	65°C	Pendant, Hook, Hood	
	The Beast High Bay	20"	HH27-279-50-EX-X-GR	279	120/277,480	30,651	66		Div 2	A, B, C, D	Div 2	F, G	US Made	1958 Wet	65°C	Pendant, Hook, Hood	
	The Beast High Bay	20"	HH32-368-50-EX-X-GR	368	120/277,480	39,647	66		Div 2	A, B, C, D	Div 2	F, G	US Made	1958 Wet	65°C	Pendant, Hook, Hood	
THE mini BEAST 	The mini Beast Low Bay	14"	HL06-055-50-EX-X-GR	55	120/277,480	6,067	66		Div 2	A, B, C, D	Div 2	F, G	US Made	1958 Wet	65°C	Pendant, Hook	
	The mini Beast Low Bay	14"	HL12-104-50-EX-X-GR	104	120/277,480	13,011	66		Div 2	A, B, C, D	Div 2	F, G	US Made	1958 Wet	65°C	Pendant, Hook	
	The mini Beast Low Bay	14"	HL16-170-50-EX-X-GR	170	120/277,480	19,058	66		Div 2	A, B, C, D	Div 2	F, G	US Made	1958 Wet	65°C	Pendant, Hook	
THE Keeper 	Explosion-Proof Linear	26" x 4"	HTL2-040-50-XXX-X	40	120 or 277	4,000	67/68		Div 1	B, C, D	Div 2	F, G		NEMA 6/6P	-65°C to 100°C	Wall, Hanging, Stanchion, Pendant	
THE Monitor 	Explosion-Proof Bay	9" Dia.	HTR9-060-50-XXX-X	60	120 or 277	6,000	67/68		Div 1	B, C, D	Div 1	E, F, G		NEMA 6/6P ABS	-65°C to 100°C	Hanging, Tripod, Wall, Ceiling Stanchion, Pendant, Tripod, Reflector	
	Explosion-Proof Bay	9" Dia.	HTR9-060-50-480-X	60	480	6,000	67/68		Div 1	B, C, D	Div 1	E, F, G		NEMA 6/6P ABS	-65°C to 100°C	Hanging, Tripod, Wall, Ceiling Stanchion, Pendant, Tripod, Reflector	
	Explosion-Proof Bay	9" Dia.	HTR9-080-50-XXX-X	80	120 or 277	8,000	67/68		Div 1	B, C, D	Div 1	E, F, G		NEMA 6/6P ABS	-65°C to 100°C	Hanging, Tripod, Wall, Ceiling Stanchion, Pendant, Tripod, Reflector	
	Explosion-Proof Bay	9" Dia.	HTR9-080-50-480-X	80	480	8,000	67/68		Div 1	B, C, D	Div 1	E, F, G		NEMA 6/6P ABS	-65°C to 100°C	Hanging, Tripod, Wall, Ceiling Stanchion, Pendant, Tripod, Reflector	
	Explosion-Proof Bay	9" Dia.	HTR9-100-50-XXX-X	100	120 or 277	10,000	67/68		Div 1	B, C, D	Div 1	E, F, G		NEMA 6/6P ABS	-65°C to 100°C	Hanging, Tripod, Wall, Ceiling Stanchion, Pendant, Tripod, Reflector	
	Explosion-Proof Bay	9" Dia.	HTR9-100-50-480-X	100	480	10,000	67/68		Div 1	B, C, D	Div 1	E, F, G		NEMA 6/6P ABS	-65°C to 100°C	Hanging, Tripod, Wall, Ceiling Stanchion, Pendant, Tripod, Reflector	
THE Lookout 	Explosion-Proof Bay	7" Dia.	HTR7-040-50-XXX-X	40	120 or 277	4,000	67/68		Div1 & 2	A, B, C, D	Div 1	E, F, G		NEMA 6/6P ABS	-20°C to 100°C	Hanging, Wall, Pendant, Stanchion, Ceiling, Stand, Reflector	
	Explosion-Proof Bay	7" Dia.	HTR7-040-50-480-X	40	480	4,000	67/68		Div1 & 2	A, B, C, D	Div 1	E, F, G		NEMA 6/6P ABS	-20°C to 100°C	Hanging, Wall, Pendant, Stanchion, Ceiling, Stand, Reflector	
	Explosion-Proof Bay	7" Dia.	HTR7-060-50-XXX-X	60	120 or 277	6,000	67/68		Div1 & 2	A, B, C, D	Div 1	E, F, G		NEMA 6/6P ABS	-20°C to 100°C	Hanging, Wall, Pendant, Stanchion, Ceiling, Stand, Reflector	
	Explosion-Proof Bay	7" Dia.	HTR7-060-50-480-X	60	480	6,000	67/68		Div1 & 2	A, B, C, D	Div 1	E, F, G		NEMA 6/6P ABS	-20°C to 100°C	Hanging, Wall, Pendant, Stanchion, Ceiling, Stand, Reflector	
THE Guard 	Explosion-Proof Bay	11" Dia.	HT11-120-50-XXX-X	120	120 or 277	12,000	67/68		Div 2	A, B, C, D	Div 2	F, G		NEMA 6/6P ABS	-65°C to 100°C	Hanging, Wall, Pendant, Stanchion, Ceiling, Stand	
	Explosion-Proof Bay	11" Dia.	HT11-120-50-480-X	120	480	12,000	67/68		Div 2	A, B, C, D	Div 2	F, G		NEMA 6/6P ABS	-65°C to 100°C	Hanging, Wall, Pendant, Stanchion, Ceiling, Stand	
	Explosion-Proof Bay	11" Dia.	HT11-140-50-XXX-X	140	120 or 277	14,000	67/68		Div 2	A, B, C, D	Div 2	F, G		NEMA 6/6P ABS	-65°C to 100°C	Hanging, Wall, Pendant, Stanchion, Ceiling, Stand	
	Explosion-Proof Bay	11" Dia.	HT11-140-50-480-X	140	480	14,000	67/68		Div 2	A, B, C, D	Div 2	F, G		NEMA 6/6P ABS	-65°C to 100°C	Hanging, Wall, Pendant, Stanchion, Ceiling, Stand	
THE Attendant 	All Purpose Low Bay	8" x 5"	HTRT-040-50-XXX-X	40	120 or 277	4,000	67/68		Div 2	A, B, C, D	N/A			NEMA 6/6P ABS	-65°C to 100°C	Hanging, Wall, Pendant, Stanchion, Ceiling, Stand	
	All Purpose Low Bay	8" x 5"	HTRT-040-50-480-X	40	480	4,000	67/68		Div 2	A, B, C, D	N/A			NEMA 6/6P ABS	-65°C to 100°C	Hanging, Wall, Pendant, Stanchion, Ceiling, Stand, Hood	
THE Officer 	THE Officer 1	Explosion-Proof Bay	13' x 11.5"	HNS1-080-50-U-X	80	120 - 277	10,400	66	DLC P	Div 1	C, D	N/A		UL1598A	-40°C to 60°C	Floor, Ceiling, Wall	
		Explosion-Proof Bay	13' x 11.5"	HNS1-100-50-U-X	100	120 - 277	13,000	66	DLC P	Div 1	C, D	N/A		UL1598A	-40°C to 60°C	Floor, Ceiling, Wall	
		Explosion-Proof Bay	13' x 11.5"	HNS1-150-50-U-X	150	120 - 277	19,500	66	DLC P	Div 1	C, D	N/A		UL1598A	-40°C to 60°C	Floor, Ceiling, Wall	
	THE Officer 2	Explosion-Proof Bay	13' x 11.5"	HNS2-080-50-U-X	80	120 - 277	10,400	66	DLC P	Div 2	A, B, C, D	Div 2	F, G	Class 3	UL1598A	-40°C to 60°C	Floor, Ceiling, Wall
		Explosion-Proof Bay	13' x 11.5"	HNS2-100-50-U-X	100	120 - 277	13,000	66	DLC P	Div 2	A, B, C, D	Div 2	F, G	Class 3	UL1598A	-40°C to 60°C	Floor, Ceiling, Wall
		Explosion-Proof Bay	13' x 11.5"	HNS2-150-50-U-X	150	120 - 277	19,500	66	DLC P	Div 2	A, B, C, D	Div 2	F, G	Class 3	UL1598A	-40°C to 60°C	Floor, Ceiling, Wall
THE Sentry 	Explosion-Proof Bay	10" Dia.	HNRO-045-50-U-X	45	120 - 277	6,750	66/Wet	DLC	Div 2	A, B, C, D	Div 1 & 2	E, F, G	Class 3 Div 1	UL1598A	-40°C to 55°C	Side, Bracket, Wall, Stanchion, Pendant, Ceiling	
	Explosion-Proof Bay	10" Dia.	HNRO-065-50-U-X	65	120 - 277	9,750	66/Wet	DLC	Div 2	A, B, C, D	Div 1 & 2	E, F, G	Class 3 Div 1	UL1598A	-40°C to 55°C	Side, Bracket, Wall, Stanchion, Pendant, Ceiling	
THE Protector 	Explosion-Proof Linear 2 Foot (24")	24" x 7"	HNL2-040-50-X-X	40	120-277,480	5,200	Wet	DLC	Div 2	A, B, C, D	Div 1 Div 2	E, F, G F, G	Class 3 Div 1	UL1598A	-40°C to 55°C	Ceiling, Wall, Stanchion, Ring	
	Explosion-Proof Linear 4 Foot (48")	48" x 7"	HNL4-080-50-X-X	80	120-277,480	10,400	Wet	DLC	Div 2	A, B, C, D	Div 1 Div 2	E, F, G F, G	Class 3 Div 1	UL1598A	-40°C to 55°C	Ceiling, Wall, Stanchion, Ring	
THE Warden 	Explosion-Proof Bay	8" x 8"	HCS8-040-50-U-X	28	120-277,480	3,600	68	DLC	Div 2	A, B, C, D	N/A		No	-30°C to 50°C	Pendant, Bracket, Floor, Ceiling, Arm 45° & 90°		
	Explosion-Proof Bay	12" x 12"	HCS12-100-50-U-X	100	120-277,480	11,701	68	DLC	Div 2	A, B, C, D	N/A		No	-30°C to 50°C	Pendant, Bracket, Floor, Ceiling, Arm 45° & 90°		
	Explosion-Proof Bay	16" x 16"	HCS16-150-50-U-X	150	120-277,480	21,313	68	DLC	Div 2	A, B, C, D	N/A		No	-30°C to 50°C	Pendant, Bracket, Floor, Ceiling, Arm 45° & 90°		

To Access more information that pertains to **Class & Group** designations, Click appropriate Icon below

-  **Class I Division 1 Groups A, B, C & D**
Flammable Gases & Vapors
-  **Class I Division 2 Groups A, B, C & D**
Flammable Gases & Vapors
-  **Class II Division 1 Groups E, F & G**
Combustible Dusts
-  **Class II Division 2 Groups E, F & G**
Combustible Dusts
-  **Class III Division 1**
Easily ignitable fibers or materials producing combustible flyings are handled, manufactured or used.
-  **Class III Division 2**
Easily ignitable fibers are stored or handled, other than in the process of manufacture.

HazLoc Chart Legend

Made in America "Beast"

Division 1 rating

Division 2 rating

Temperature Conversions

50°C	122°F	55°C	131°F
60°C	140°F	65°C	149°F
85°C	185°F	100°C	212°F

SOLAS RAY™ LIGHTING
1524 Jackson Street
Anderson, IN 46016
765-298-8030

Specifications are subject to change without advanced notice.