

The GUIDE Hazardous Location Exit Lighting

HJJES

120 - 277vAC



Cat. #	Type
Notes	

DESIGNATIONS

UL844

KEY FEATURES AND BENEFITS

- Class I Division 1 & 2 (Flammable Gases & Vapors).
- Class II Division 1 & 2 (Flammable Gases & Vapors).
- Class III (Combustible Flyings & Fibers).
- Self-Testing Microprocessor.
- Three Hour Battery Backup.
- High vibration / Anti-resonance design.
- Permissible temperature -20°C (-4°F) to 60°C (140°F).
- Corrosion proof – Coated aluminum alloy (copper free) housing.
- Low Wattage requirements of 3w and 5w..
- Paint/Spray listed for use in paint or powder booths.
- Suitable for Wet Locations
- 5-Year limited warranty.

SPECIFICATIONS

NAME	The Guide Exit Sign
Category	Hazardous Area Exit Lighting
Model #	HJJES
Voltage	120 - 277vAC
Ambient Temperatures	-20°C (-4°F) to 60°C (140°F)
Housing	Coated Marine Grade Aluminum Alloy
Color	Gray with Red Letters
Wattage	3w, 5w
Lifetime	50,000 hr. at L ₇₀
Power Factor	>0.98

Weight	15 lbs.
Dimensions	15.59" W x 18.15" H x 4.5" D
NPT	3/4"
Warranty	5-Year Limited

PRODUCT ORDERING SELECTION

Model #	Wattage	Order #
HJJES-003	3 Watts	<input type="checkbox"/> HJJES-003-R-U-FG
HJJES-005	5 Watts	<input type="checkbox"/> HJJES-005-R-U-FG

DIMENSIONS

