

REMOTE CAPABLE WET LOCATION Emergency Light

RCWLUE

120 - 277vAC

Cat. #	Type
Notes	




DESIGNATIONS



KEY FEATURES AND BENEFITS

- Sealed and gasketed weather proof lamps with high performance chrome-plated metallized reflector and tempered glass lenses for optimal light distribution.
- Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in gray or black finish.

DIMENSIONS



SPECIFICATIONS

ELECTRICAL

- Dual 120/277 voltage.
- Two fully adjustable, semi-recessed ultra bright, 7.2 watt MR-16 halogen lamp heads standard.
- High performance MR16 halogen lamps with smooth metallized reflector and glass lens for optimal light distribution.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- LVD (low voltage disconnect) prevents battery from deep discharge.
- 6V maintenance-free, rechargeable sealed lead acid battery.
- Internal solid-state transfer switch automatically connects the internal battery to lamp heads for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

- Universal knockout pattern on back plate for wall mount snaps into place making internal electrical connections.

HOUSING

- Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in gray or black finish.

- Fully gasketed clear polycarbonate cover offers protection against wet, non-hazardous dust, corrosive atmospheres and to water spray or splashing water locations.

OPTIONS

- HTR: Optional internal heater for cold temperature (-9°C – 40°C).
- CW: Optional internal heater / battery blanket for extreme cold temperatures, (-25°C – 50°C MR-16 halogen) (-25°C – 40°C LED).
- LED: 3.3W high performance MR-16 base LED lamps for increased center-to-center spacing.
- CEC: Certified to CEC under Title 20 Regulations.
- PLED: 5.0W high performance MR-16 base LED lamps for premium center-to-center spacing.

WARRANTY / LISTING

- Five year warranty on all electronics and housing.
- Battery prorated for two years.

CERTIFICATIONS

- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for wet locations (20°C – 40°C).

PRODUCT ORDERING SELECTION

RCWLUE	—	—	—
Model	Housing Color	Options	
RCWLUE	<input type="checkbox"/> Blank - Gray <input type="checkbox"/> B - Black	<input type="checkbox"/> CEC - Title 20 Compliance	

