

# IBVT Series

## The BARRIER™

Vapor Tight Globe Light

Cat. #	Type
Notes	

High Vibration  
RESISTANCE



Wall Mount



Ceiling Mount



Pendant Mount



### CERTIFICATIONS / RATINGS



CERTIFIED  
UL 1598

MARINE  
UL 1598 A

IP66

### KEY FEATURES AND BENEFITS

- Ambient temperature capabilities: -30°C to 50°C (122°F).
- Corrosion resistant, marine grade, polyester thermoplastic housing.
- Impact resistant tempered glass globe with plastic guard.
- Neoprene gaskets seal each mounting option.
- Optional lens selection includes; red, green, blue, white and amber.
- Clear lens standard.
- Wet location rated.
- Buy American Act compliant.

Also Available For  
Hazardous Locations  
(See HBVT Series)


### SPECIFICATIONS

<b>Voltage</b>	120-277 VAC
<b>Wattage</b>	16W
<b>Lumens</b>	1,150 Lm
<b>Color Temp</b>	5000 Kelvin
<b>Ambient Temperature</b>	-30°C (-22°F) to 50°C (122°F)
<b>T-Rating</b>	T3
<b>Housing</b>	Polyester thermoplastic
<b>Color</b>	Gray
<b>Lens</b>	Tempered glass globe
<b>Lifetime</b>	50,000 hrs rated life
<b>CRI</b>	>80
<b>Efficacy</b>	72 Lm/W
<b>Power Factor</b>	>0.95
<b>Protection</b>	IP66
<b>NPT</b>	3/4"
<b>Warranty</b>	5 Year Limited Warranty

### WEIGHTS AND DIMENSIONS

#### WEIGHT

3.2 Lbs.



### PRODUCT ORDERING SELECTION

<b>IBVT</b>	<b>016</b>	<b>50</b>	<b>U</b>		
<b>Series/Length</b>	<b>Watts</b>	<b>Kelvin</b>	<b>Voltage</b>	<b>Lens Options</b>	<b>Mounting Options</b>
<input checked="" type="checkbox"/> IBVT	<input checked="" type="checkbox"/> 016 - 16W	<input checked="" type="checkbox"/> 50 - 5000K	<input checked="" type="checkbox"/> U - 120-277 VAC	<input type="checkbox"/> C - Clear (Standard) <input type="checkbox"/> G - Green <input type="checkbox"/> W - White	<input type="checkbox"/> R - Red <input type="checkbox"/> B - Blue <input type="checkbox"/> A - Amber <input type="checkbox"/> WM - Wall Mount <input type="checkbox"/> CM - Ceiling Mount <input type="checkbox"/> PM - Pendant Mount