


HJHL Series

The FLYER™

Hazardous Location LED Lighting



Available in 4' and 2' lengths.



High Vibration
RESISTANCE



5935 West 84th St. | Indianapolis, IN 46278 | 1-800-840-5635 | www.SolasRay.com

Cat. #	Type
Notes	

CERTIFICATIONS / RATINGS



CLASS / DIVISION

- Class I, Div 2, Groups A, B, C, D
- Class II, Div 1, Groups E, F, G
- Class II, Div 2, Groups F, G
- Class III

KEY FEATURES AND BENEFITS

- -40°C to 60°C (140°F) ambient temperature capabilities.
- * DLC V5.1 Standard (4000K/5000K with 120° beam angle only)
- Internal EM battery option (15W / 90 min).
- Heavy-duty design with high impact resistance.
- Corrosion proof - coated copper free aluminum housing.
- Marine rated gray powder coated finish.
- Stainless steel hardware and mounting bracket.
- 3 connection cable entry points.

SPECIFICATIONS

Voltage	120-277 VAC / 200-480 VAC
Wattage	20W / 40W / 60W / 80W
Color Temp	4000 / 5000 Kelvin
Ambient Temperature	-40°C (-40°F) to 60°C (140°F) (-10°C to 60°C with EM Battery)
Housing	Coated copper free aircraft aluminum
Color	Gray
Lens	Tempered glass with polycarbonate lens
Lifetime	70,000 hrs L70
CRI	80

Beam Angles	120° x 120°
Efficacy	up to 140 lm/W
Protection	IP66
Entrance Thread	3/4" NPT
Warranty	5 Year Limited Warranty - Fixture 3 Year Limited Warranty - Battery

LUMENS

20W	40W	60W	80W
2,800	5,600	8,400	11,200

PRODUCT ORDERING SELECTION

<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	120	<input type="text"/>	<input type="text"/>
Series/Length	Watts	Kelvin	Voltage	Beam Angle	Mounting Options	Other Options
<input type="checkbox"/> HJHL22 (2 ft)	<input type="checkbox"/> 020 - 20w	<input type="checkbox"/> 40 - 4000K	<input type="checkbox"/> U - 120-277 VAC	<input checked="" type="checkbox"/> 120 - 120°	<input type="checkbox"/> HJUB - Universal Yoke Bracket	<input type="checkbox"/> EM - Emergency Battery Backup - 15W (120-277VAC models only)
	<input type="checkbox"/> 040 - 40w	<input type="checkbox"/> 50 - 5000K	<input type="checkbox"/> 48 - 200-480 VAC		<input type="checkbox"/> HJPP - Pendant Pipe	
<input type="checkbox"/> HJHL42 (4 ft)	<input type="checkbox"/> 040 - 40w					
	<input type="checkbox"/> 060 - 60w					
	<input type="checkbox"/> 080 - 80w					

HJHL Series

The FLYER™



5935 West 84th St. | Indianapolis, IN 46278 | 1-800-840-5635 | www.SolasRay.com

MOUNTING OPTIONS

#HJUB - Universal Yoke Bracket

Universal yoke bracket may be used as a ceiling mount or wall mount.



Features +/- 90° adjustable angle.

#HJPP - Pendant Pipe



EM BATTERY OPTION (INTERNAL)




Available for 120-277VAC models only.

Input Rating	AC 120-277V
Output Wattage	15W
Battery Capacity	2000 mAh
Battery Run-time	90 minutes
Charge Time	≥ 24 hours
Ambient Temperature	-10°C (14°F) to 60°C (140°F)
Battery Warranty	3 Year Limited Warranty



WEIGHTS AND DIMENSIONS

2' MODELS



WEIGHTS

2'	4'
8.9 lb	12.2 lb

4' MODELS

