

# WWC Series

## WALL PACK

Heavy Duty Full Cut-Off



### SPECIFICATIONS

<b>Voltage</b>	120-277vAC
<b>Wattage</b>	Selectable 30w / 45w / 60w / 70w
<b>Lumens</b>	Selectable (see chart)
<b>Color Temp</b>	Selectable 3000 / 4000 / 5000 Kelvin
<b>Housing</b>	Cast aluminum
<b>Lens</b>	Polycarbonate
<b>Efficacy</b>	Up to 130 lm/w
<b>CRI</b>	70
<b>Power Factor</b>	0.95
<b>Driver Efficacy</b>	90%
<b>Beam Angle</b>	82° x 102°
<b>Life Span</b>	75,000 hrs
<b>Ambient Temperature</b>	-30°C (-22°F) to 45°C (113°F)
<b>Warranty</b>	5 Year Limited Warranty

#### LUMENS

Setting	30w	45w	60w	70w
<b>Lumens</b>	4,216	6,139	7,882	8,980

### PRODUCT ORDERING SELECTION

<b>WWC</b>	-	<b>34567</b>	-	<b>345K</b>	-	<b>U</b>	-	<b>Z</b>	-	<b>P</b>	-	
<b>Series</b>		<b>Watts</b>		<b>Kelvin</b>		<b>Voltage</b>		<b>Body Color</b>		<b>Photocell</b>		<b>Optional Emergency Backup</b>
<input checked="" type="checkbox"/> WWC		<input checked="" type="checkbox"/> 34567 - Selectable (30w / 45w / 60w / 70w)		<input checked="" type="checkbox"/> 345K - Selectable (3000K / 4000K / 5000K)		<input checked="" type="checkbox"/> U - 120-277 vAC		<input checked="" type="checkbox"/> Z - Bronze		<input checked="" type="checkbox"/> P - Photocell (standard)		<input type="checkbox"/> BLD-8 - 8W Emergency Backup <input type="checkbox"/> BLD-15 - 15W Emergency Backup



5935 West 84th St. | Indianapolis, IN 46278 | 1-800-840-5635 | www.SolasRay.com

Cat. #	Type
Notes	

### CERTIFICATIONS / RATINGS



**IP65**

### KEY FEATURES AND BENEFITS

- Field adjustable wattage 30w / 45w / 60w / 70w.
- Field adjustable color temperature 3000K / 4000K / 5000K.
- Photocell included standard - comes with cover for non-photocell operation.
- Excellent optics for greatly improved light utilization and even distribution.
- High efficiency LED (up to 130 lm/w).
- Long life (75,000 hrs).
- 1-10V dimming.



Wattage and color temp. controls.

Included photocell



Included photocell cover



### WEIGHTS AND DIMENSIONS

